

MULTI - PAIR, PVC INSULATION INDIVIDUAL AND COLLECTIVE SCREEN, PVC - SHEATHED CABLES

RE-Y(st)Y-PIMF 300 / 500 V

No. of pair	No. strand x diameter	Insulation thickness	sheath thickness	Overall diameter .Approx	Approx. weight
mm2	N x d mm	mm	mm	mm	Kg/km
0.5 mm2 (flexible)					
2x2x0.5	16x0.2	0.6	1.1	11.2	120
5x2x0.5	16x0.2	0.6	1.2	14.6	210
10x2x0.5	16x0.2	0.6	1.3	19.2	370
15x2x0.5	16x0.2	0.6	1.5	22.5	540
20x2x0.5	16x0.2	0.6	1.5	26	690
30x2x0.5	16x0.2	0.6	1.7	31.2	950
50x2x0.5	16x0.2	0.6	2	35.5	1650
0.75 mm2 (flexible)					
2x2x0.75	24x0.2	0.6	1.1	12.2	130
5x2x0.75	24x0.2	0.6	1.2	16	250
10x2x0.75	24x0.2	0.6	1.3	21.2	450
15x2x0.75	24x0.2	0.6	1.5	25	650
20x2x0.75	24x0.2	0.6	1.7	28.6	850
30x2x0.75	24x0.2	0.6	2	34.8	1260
50x2x0.75	24x0.2	0.6	2.2	44	2000
1.5 mm2 (stranded)					
2x2x1.5	7x0.52	0.6	1.2	13.8	190
5x2x1.5	7x0.52	0.6	1.3	17.8	360
10x2x1.5	7x0.52	0.6	1.5	24.2	670
15x2x1.5	7x0.52	0.6	1.7	28.4	970
20x2x1.5	7x0.52	0.6	2	32	1250
30x2x1.5	7x0.52	0.6	2.2	39	1840
50x2x1.5	7x0.52	0.6	2.4	49.2	2940