

**XLPE INSULATED PVC SHEATHED
MULTI CORE SCREENED CABLES
N2XCY, N2XCWY, N2XSY 0.6 /1KV**

Size	No. strand x diameter	Insulation thickness	Sheath thickness	Approx. Overall diameter	Approx. weight
mm ²	N x d mm	mm	mm	mm	Kg/km
2x1.5/1.5 rm	7x0.52 12x0.40	0.7	1.8	13.2	205
2x2.5/2.5 rm	7x0.67 12x0.52	0.7	1.8	14.2	275
2x4/4 rm	7x0.85 19x0.52	0.7	1.8	15.5	358
2x6/6 rm	7x1.04 12x0.81	0.7	1.8	16.7	448
2x10/10 rm	7x1.35 19x0.81	0.7	1.8	18.9	614
2x16/16 rm	7x1.70 16x1.13	0.7	1.8	21.3	870
2x25/25 rm	7x2.14 25x1.13	0.9	1.8	25	1275
2x35/35 rm	7x2.52 35x1.13	0.9	1.8	27.6	1640
3x1.5/1.5 rm	7x0.52 12x0.40	0.7	1.8	13.4	230
3x2.5/2.5 rm	7x0.67 12x0.52	0.7	1.8	14.4	296
3x4/4 rm	7x0.85 19x0.52	0.7	1.8	16	410
3x6/6 rm	7x1.04 12x0.81	0.7	1.8	17.2	500
3x10/10 rm	7x1.35 19x0.81	0.7	1.8	19.6	710
3x16/16 rm	7x1.70 16x1.13	0.7	1.8	22	1050
3x25/25 rm	7x2.14 25x1.13	0.9	1.8	26.1	1520
3x35/35 rm	7x2.52 35x1.13	0.9	1.9	29	1980