

**XLPE INSULATED AERIAL
BUNDLED CABLES - ABC
NFA2X 0.6 / 1 KV**

Size	No. strand x diameter	Insulation thickness	Approx. Overall diameter	Approx. weight
mm ²	N x dmm	mm	mm	Kg/km
1x25+16+25	7x2.22 7x1.73	1.3 - 1.1	15	330
1x35+16+35	7x2.62 7x1.73	1.3 - 1.1	22	386
3x35+16+35	7x2.62 7x1.73	1.3 - 1.1	27	640
3x50+16+35	7x3.09 7x1.73	1.5 - 1.1	29	785
3x70+25+70	19x2.22 7x2.22	1.5 - 1.3	35	1155
3x95+25+70	19x2.62 7x2.22	1.7 - 1.3	38	1426
3x35+16+25+25	7x2.62 7x1.73 7x2.22	1.3 - 1.1 - 1.3	28	730
3x50+16+35+25	7x3.09 7x1.73 7x2.62	1.3 - 1.1 - 1.5	31	906
3x70+16+50+25	19x2.22 7x1.73 7x3.09	1.5 - 1.1 - 1.5	34	1160
3x95+25+70+25	19x2.62 7x2.22 19x2.22	1.5 - 1.3 - 1.7	39	1530