

MICA GLASS TAPE, XLPE INSULATED ARMoured LSFOH SHEATHED FIRE RESISTANCE CABLES

N2XHRH 0.6 / 1 KV

Size	No. strand x diameter	Insulation thickness	Armour wire diameter	Sheath thickness	Approx. Overall diameter	Approx. weight
mm ²	N x d mm	mm	mm	mm	mm	Kg/km
2x1.5 rm	7x0.52	0.7	0.9	1.8	15.4	170
2x2.5 rm	7x0.67	0.7	0.9	1.8	16	230
2x4 rm	7x0.85	0.7	0.9	1.8	17.4	282
2x6 rm	7x1.04	0.7	1.2	1.8	18.4	344
3x1.5 rm	7x0.52	0.7	0.9	1.8	16	222
3x2.5 rm	7x0.67	0.7	0.9	1.8	16.8	264
3x4 rm	7x0.85	0.7	1.2	1.8	18.4	332
3x6 rm	7x1.04	0.7	1.2	1.8	19.5	404
4x1.5 rm	7x0.52	0.7	0.9	1.8	16.8	242
4x2.5 rm	7x0.67	0.7	1.2	1.8	17.8	288
4x4 rm	7x0.85	0.7	1.2	1.8	19.5	378
4x6 rm	7x1.04	0.7	1.2	1.8	21.6	472
5x1.5 rm	7x0.52	0.7	0.9	1.8	18.2	540
7x1.5 rm	7x0.52	0.7	1.2	1.8	19.5	650
10x1.5 rm	7x0.52	0.7	1.2	1.8	24.3	830
12x1.5 rm	7x0.52	0.7	1.6	1.8	25	1070
19x1.5 rm	7x0.52	0.7	1.6	1.8	28.5	1380
27x1.5 rm	7x0.52	0.7	1.6	1.9	34	1980



37x1.5 rm	7x0.52	0.7	2	1.9	38.4	2520
48x1.5 rm	7x0.52	0.7	2	2	43.6	3040
5x2.5 rm	7x0.67	0.7	0.9	1.8	19.3	620
7x2.5 rm	7x0.67	0.7	1.2	1.8	21.8	830
10x2.5 rm	7x0.67	0.7	1.6	1.8	26.4	1140
12x2.5 rm	7x0.67	0.7	1.6	1.8	27.2	1250
19x2.5 rm	7x0.67	0.7	1.6	1.8	32.6	1840
27x2.5 rm	7x0.67	0.7	2	1.8	37.6	2520
37x2.5 rm	7x0.67	0.7	2	1.9	42	3100
48x2.5 rm	7x0.67	0.7	2	2.1	48.5	4140