

MULTI-PAIR, MICA GLASS TAPE, XLPE INSULATION INDIVIDUAL AND COLLECTIVE SCREEN, LSFOH SHEATHED INSTRUMENT CABLES

RE-2X(st)H-PIMF 300 / 500 V

Size	No. strand x diameter	Insulation thickness	Sheath thickness	Approx. Overall diameter	Approx. weight
mm ²	N x d mm	mm	mm	mm	Kg/km
0.75 mm ² (stranded)					
1x2x0.75	7x0.37	0.6	0.9	7.6	78
2x2x0.75	7x0.37	0.6	0.9	12.6	144
5x2x0.75	7x0.37	0.6	1.2	16.8	262
10x2x0.75	7x0.37	0.6	1.4	22.4	446
15x2x0.75	7x0.37	0.6	1.5	26	660
20x2x0.75	7x0.37	0.6	1.6	29.6	850
30x2x0.75	7x0.37	0.6	1.7	36	1240
1 mm ² (stranded)					
1x2x1	7x0.43	0.6	1	8.8	104
2x2x1	7x0.43	0.6	1.1	15.2	218
5x2x1	7x0.43	0.6	1.2	19.6	360
10x2x1	7x0.43	0.6	1.5	27	670
15x2x1	7x0.43	0.6	1.6	32.2	990
20x2x1	7x0.43	0.6	1.7	35.6	1240
30x2x1	7x0.43	0.6	2	43	1840
1.5 mm ² (stranded)					
1x2x1.5	7x0.52	0.6	1	8.8	104
2x2x1.5	7x0.52	0.6	1.2	15.2	218
5x2x1.5	7x0.52	0.6	1.4	19.6	360
10x2x1.5	7x0.52	0.6	1.6	27	670



15x2x1.5	7x0.52	0.6	1.8	32.2	990
20x2x1.5	7x0.52	0.6	1.9	35.6	1240
30x2x1.5	7x0.52	0.6	2.2	43	1840
2.5 mm2 (stranded)					
1x2x2.5	7x0.67	0.7	1.2	10.2	116
2x2x2.5	7x0.67	0.7	1.4	16.8	244
5x2x2.5	7x0.67	0.7	1.5	20.8	400
10x2x2.5	7x0.67	0.7	1.7	29.8	740
15x2x2.5	7x0.67	0.7	1.9	35	1100
20x2x2.5	7x0.67	0.7	2.1	40.6	1380
30x2x2.5	7x0.67	0.7	2.4	47.4	2060