

HIGH FREQUENCY COAXIAL CABLES

Symbol	Inner conductor	Insulation thickness	Braid shield Inner	Braid shield Outer	Sheath thickness	Approx. Overall diameter	Approx. weight
	N x dmm	mm	N x dmm	N x dmm	mm	mm	Kg/km
0.8D - 2V	1x0.26	0.27	16x3x0.10	-	0.35	2	8
1.5D - 2V	7x0.18	0.53	16x5x0.10	-	0.4	2.9	11
2.5D - 2V	1x0.8	0.95	16x7x0.12	-	0.5	4.3	35
3D - 2V	7x0.32	0.02	24x5x0.14	-	0.8	5.3	44
5D - 2V	1x1.4	1.7	24x50.14	-	0.9	7.3	80
8D - 2V	1x1.4	1.7	24x7x0.14	24x7x0.14	0.9	8	110
10D - 2V	7x0.8	2.7	24x8x0.18	-	1.2	11.1	180
	1x2.9	3.4	24x10x0.20	-	1.2	13.1	260
1.5C - 2V	1x0.26	0.67	16x5x0.10	-	0.4	2.9	13
2.5C - 2V	1x1.4	1	16x6x0.10	-	0.5	4	25
3C - 2V	1x0.5	1.3	24x5x0.14	-	0.8	5.4	42
5C - 2V	1x0.8	2.05	24x7x0.14	-	0.9	7.4	74
5C - 2W	1x0.8	2.05	24x7x0.14	24x7x0.14	1	8.3	120
7C - 2V	7x0.4	3.05	24x8x0.18	-	1.1	10.4	140
10C - 2V	7x0.5	3.05	24x10x0.20	-	1.3	13	220