

PVC INSULATED NON SHEATHED SINGLE CORE CABLES

NYA 300 / 500 , 450 / 750 V

Size	No. strand x diameter	Insulation thickness	Approx overall diameter	Approx . weight
mm2	N x dmm	mm	Kg/km	kg/km
0.5	1x0.8	0.6	2.1	9
0.75	1x0.98	0.6	2.2	11
1	1x1.13	0.6	2.4	14
1.5	1x1.38	0.7	2.9	21
1.5	7x0.52	0.7	3.1	22
2.5	1x1.78	0.8	3.5	33
2.5	7x0.67	0.8	3.7	34
4	1x2.25	0.8	3.9	48
4	7x0.85	0.8	4.2	51
6	1x2.76	0.8	4.4	67
6	7x1.04	0.8	4.8	71
10	7x1.35	1	6.2	119
16	7x1.7	1	7.2	179
25	7x2.14	1.2	8.9	280
35	7x2.52	1.2	10.1	375
50	19x1.78	1.4	11.8	506
70	19x2.14	1.4	13.6	714
95	19x2.52	1.6	16.0	980
120	37x2.03	1.6	17.6	1225
150	37x2.25	1.8	19.5	1505
185	37x2.52	2	21.8	1890
240	37x2.88	2.2	24.7	2410
300	61x2.5	2.4	37.6	3014