

## کابل‌های قدرت تک رشته‌ای با عایق و روکش PVC NYY 0.6 / 1 KV

سایز	قطر * تعداد رشته	ضخامت عایق	ضخامت روکش	قطر کلی تقریبی	وزن تقریبی
mm <sup>2</sup>	N x dmm	mm	mm	mm	Kg/km
1x4 re	1x2.26	1	1.4	7.1	82
1x4 rm	7x0.85	1	1.4	7.4	86
1x6 re	1x2.78	1	1.4	7.6	110
1x6 rm	7x1.04	1	1.4	7.9	116
1x10 re	1x3.57	1	1.4	8.4	152
1x10 rm	7x1.35	1	1.4	8.9	160
1x16 rm	7x1.7	1	1.4	9.9	226
1x25 rm	7x2.14	1.2	1.4	11.6	333
1x35 rm	7x2.52	1.2	1.4	12.8	436
1x50 rm	19x1.78	1.4	1.4	14.5	570
1x70 rm	19x2.17	1.4	1.4	16.7	780
1x95 rm	19x2.52	1.6	1.5	18.9	1080
1x120 rm	37x2.03	1.6	1.5	20.6	1330
1x150 rm	37x2.25	1.8	1.6	22.8	1620
1x185 rm	37x2.52	2	1.7	25.2	2070
1x240 rm	37x2.88	2.2	1.8	28.5	2640
1x300 rm	61x2.50	2.4	1.9	31.5	3240
1x400 rm	61x2.85	2.6	2	35.1	4170
1x500 rm	61x3.2	2.8	2.1	38.8	5210