

## کابل‌های قدرت تک رشته‌ای با عایق XLPE و روکش PVC

## N2XY 0.6 / 1 KV

سایز	قطر * تعداد رشته	ضخامت عایق	ضخامت روکش	قطر کلی تقریبی	وزن تقریبی
mm <sup>2</sup>	N x d mm	mm	mm	mm	Kg/km
1x4 re	1x2.26	0.7	1.4	6.5	76
1x4 rm	7x0.85	0.7	1.4	6.8	80
1x6 re	1x2.78	0.7	1.4	7	98
1x6 rm	7x1.04	0.7	1.4	7.3	105
1x10 re	1x3.57	0.7	1.4	7.8	140
1x10 rm	7x1.35	0.7	1.4	8.3	145
1x16 rm	7x1.7	0.7	1.4	9.3	210
1x25 rm	7x2.14	0.9	1.4	11	310
1x35 rm	7x2.52	0.9	1.4	12.2	410
1x50 rm	19x1.78	1	1.4	13.7	530
1x70 rm	19x2.17	1.1	1.4	16.1	770
1x95 rm	19x2.52	1.1	1.5	17.8	1010
1x120 rm	37x2.03	1.2	1.5	19.8	1270
1x150 rm	37x2.25	1.4	1.6	21.8	1550
1x185 rm	37x2.52	1.6	1.6	24.2	1940
1x240 rm	37x2.88	1.7	1.7	27.4	2510
1x300 rm	61x2.50	1.8	1.8	30	3110
1x400 rm	61x2.85	2	1.9	33.5	3980
1x500 rm	61x3.2	2.2	2.1	37.4	5000