

کابل‌های ابزار دقیق تک و چند زوجی با اسکرین کلی، مسلح با زره فولادی با
عایق و روکش PVC

RE-Y(ST)YRY 300 / 500 V

تعداد جفت‌ها	قطر * تعداد رشته	ضخامت عایق	ضخامت بدینگ	قطر مفتول گالوانیزه	ضخامت روکش	قطر کلی تقریبی	وزن تقریبی
mm ²	N x d mm	mm	mm	mm	mm	mm	Kg/km
0.5 mm ² (flexible)							
1x2x0.5	16x0.2	0.6	0.8	0.9	1.3	10.6	230
2x2x0.5	16x0.2	0.6	0.8	0.9	1.3	11.6	260
5x2x0.5	16x0.2	0.6	1.1	0.9	1.5	17.2	490
10x2x0.5	16x0.2	0.6	1.2	1.2	1.6	22.4	840
15x2x0.5	16x0.2	0.6	1.3	1.6	1.7	26	1230
20x2x0.5	16x0.2	0.6	1.3	1.6	1.8	28.5	1450
30x2x0.5	16x0.2	0.6	1.5	1.6	1.9	33.4	1900
50x2x0.5	16x0.2	0.6	1.7	2	2.1	41.8	2920
0.75 mm ² (flexible)							
1x2x0.75	24x0.2	0.6	0.8	0.9	1.3	11.2	250
2x2x0.75	24x0.2	0.6	0.8	0.9	1.4	12.4	300
5x2x0.75	24x0.2	0.6	1.2	1.2	1.5	19.5	670
10x2x0.75	24x0.2	0.6	1.3	1.6	1.7	25	1190
15x2x0.75	24x0.2	0.6	1.3	1.6	1.8	28	1400
20x2x0.75	24x0.2	0.6	1.5	1.6	1.9	31.2	1720
30x2x0.75	24x0.2	0.6	1.7	2	2	37.8	2500
50x2x0.75	24x0.2	0.6	2	2.5	2.2	47.5	3920
1.5 mm ² (stranded)							
1x2x1.5	7x0.52	0.6	0.8	0.9	1.4	12.2	290
2x2x1.5	7x0.52	0.6	0.9	0.9	1.4	13.4	390
5x2x1.5	7x0.52	0.6	1.2	1.2	1.6	21.5	850
10x2x1.5	7x0.52	0.6	1.3	1.6	1.8	27.8	1460



15x2x1.5	7x0.52	0.6	1.5	1.6	1.9	31.8	1900
20x2x1.5	7x0.52	0.6	1.5	1.6	2	35	2250
30x2x1.5	7x0.52	0.6	1.7	2	2.1	42	3310
50x2x1.5	7x0.52	0.6	2.2	2.5	2.4	53	5280