

## کابل‌های افشان با عایق و روکش PVC NYMHY 300 / 500 V

سایز	قطر * تعداد رشته	ضخامت عایق	ضخامت روکش	قطر کلی تقریبی	وزن تقریبی
mm <sup>2</sup>	N x d mm	mm	mm	mm	kg/km
2x0.75	24x0.2	0.6	0.8	6.5	61
2x1	32x0.2	0.6	0.8	6.8	70
2x1.5	30x0.25	0.7	0.8	7.7	91
2x2.5	50x0.25	0.8	1	9.4	138
2x4	56x0.3	0.8	1.1	10.7	190
3x0.75	24x0.2	0.6	0.8	6.9	72
3x1	32x0.2	0.6	0.8	7.2	84
3x1.5	30x0.25	0.7	0.9	8.4	112
3x2.5	50x0.25	0.8	1.1	10.2	172
3x4	56x0.3	0.8	1.2	11.6	240
4x0.75	24x0.2	0.6	0.9	7.7	90
4x1	32x0.2	0.6	0.9	8.1	104
4x1.5	30x0.25	0.7	1	9.3	142
4x2.5	50x0.25	0.8	1.1	11.1	210
4x4	56x0.3	0.8	1.2	12.36	295
5x0.75	24x0.2	0.6	0.9	8.4	110
5x1	32x0.2	0.6	0.9	8.8	130
5x1.5	30x0.25	0.7	1.1	10.4	180
5x2.5	50x0.25	0.8	1.2	12.4	265
5x4	56x0.3	0.8	1.4	14.4	380