

کابل‌های قدرت کنترل و چند رشته‌ای مسلح با نوار فولادی  
یا آلومینیومی با عایق XLPE و روکش PVC  
N2XYBY 0.6 / 1 KV

سایز	قطر * تعداد رشته	ضخامت عایق	ضخامت نوار گالوانیزه یا آلومینیومی	ضخامت روکش	قطر کلی تقریبی	وزن تقریبی
mm <sup>2</sup>	N x dmm	mm	mm	mm	mm	Kg/km
3x1.5 rm	7x0.53	0.7	0.2	1.8	13.4	285
3x2.5 rm	7x0.67	0.7	0.2	1.8	14.4	340
3x4 rm	7x0.85	0.7	0.2	1.8	15.4	410
3x6 rm	7x1.04	0.7	0.2	1.8	16.8	530
3x10 rm	7x1.35	0.7	0.2	1.8	18.5	690
3x16 rm	7x1.7	0.7	0.2	1.8	20.4	910
3x25 rm	7x2.14	0.9	0.2	1.8	23.8	1280
3x35 rm	7x2.52	0.9	0.2	1.8	26.4	1650
3x50 sm	19x1.83	1	0.2	1.9	28.4	1970
3x70 sm	19x2.22	1.1	0.2	2	32	2640
3x95 sm	19x2.57	1.1	0.5	2.2	36.5	3865
3x120 sm	37x2.08	1.2	0.5	2.3	39.4	4670
3x150 sm	37x2.3	1.4	0.5	2.4	43.8	5660
3x185 sm	37x2.57	1.6	0.5	2.6	49	6980
3x240 sm	37x2.93	1.7	0.5	2.8	54.5	8840
3x300 sm	62x2.65	1.8	0.5	3	60	10860
3x25+16 rm	7x- 2.14 7x1.7	0.9 - 0.7	0.2	1.8	24.6	1460
3x35+16 rm	7x- 2.52 7x1.7	0.9 - 0.7	0.2	1.8	27.4	1820
3x50+25 sm	19x- 1.83 7x2.14	1 - 0.9	0.2	1.9	32	2290
3x70+35 sm	19x- 2.22 7x2.52	1.1 - 0.9	0.2	2.1	35.5	3060



3x95+50 sm	19x- 2.57 19x1.83	1.1 - 1	0.5	2.2	41	4480
3x120+70 sm	37x- 2.08 19x2.22	1.2 - 1.1	0.5	2.4	46	5540
3x150+70 sm	37x- 2.30 19x2.22	1.4 - 1.1	0.5	2.5	51	6580
3x185+95 sm	37x- 2.57 37x2.57	1.6 - 1.1	0.5	2.7	55.2	8160
3x240+120 sm	37x- 2.93 37x2.08	1.7 - 1.2	0.5	2.9	63	10360
3x300+150 sm	61x2.65 37x2.30	1.8 - 1.4	0.5	3	70	12820
4x1.5 rm	7x0.53	0.7	0.2	1.8	13.8	315
4x2.5 rm	7x0.67	0.7	0.2	1.8	14.8	380
4x4 rm	7x0.85	0.7	0.2	1.8	16	470
4x6 rm	7x1.04	0.7	0.2	1.8	18.5	620
4x10 rm	7x1.35	0.7	0.2	1.8	20	810
4x16 rm	7x1.7	0.7	0.2	1.8	22	1100
4x25 rm	7x2.14	0.9	0.2	1.8	26.2	1600
4x35 rm	7x2.52	0.9	0.2	1.9	31.4	2280
4x50 sm	19x1.83	1	0.2	2	32.6	2540
4x70 sm	19x2.22	1.1	0.5	2.2	37.3	3800
4x95 sm	19x2.57	1.1	0.5	2.3	41.8	4990
4x120 sm	37x2.08	1.2	0.5	2.4	46	6050
4x150 sm	37x2.3	1.4	0.5	2.6	51	7370
4x185 sm	37x2.57	1.6	0.5	2.8	55.8	9080
4x240 sm	37x2.93	1.7	0.5	3	63.5	11620
4x300 sm	61x2.65	1.8	0.5	3.2	71	14400
5x1.5 rm	7x0.53	0.7	0.2	1.8	14.8	360
7x1.5 rm	7x0.53	0.7	0.2	1.8	16	430
10x1.5 rm	7x0.53	0.7	0.2	1.8	19	560