

کابل‌های قدرت آلومینیومی تک و چند رشته‌ای با عایق و روکش PVC

NAYY 0.6 / 1 KV

سایز	قطر * تعداد رشته	ضخامت عایق	ضخامت غلاف	قطر کلی تقریبی	وزن تقریبی
mm ²	N x dmm	mm	mm	mm	Kg/km
1x16 rm	7x1.7	1	1.4	9.9	128
1x25 rm	7x2.14	1.2	1.4	11.6	180
1x35 rm	7x2.52	1.2	1.4	12.8	224
1x50 rm	19x1.78	1.4	1.4	14.5	288
1x70 rm	19x2.17	1.4	1.4	16.7	368
1x95 rm	19x2.52	1.6	1.5	18.9	488
1x120 rm	37x2.03	1.6	1.5	20.6	582
1x150 rm	37x2.25	1.8	1.6	22.8	700
1x185 rm	37x2.52	2	1.7	25.2	870
1x240 rm	37x2.88	2.2	1.8	28.5	1100
1x300 rm	37x34/3	2.4	1.9	31.5	1360
1x400 rm	61x2.85	2.6	2	35.1	1720
1x500 rm	61x3.2	2.8	2.1	38.8	2120
3x50 sm	19x1.83	1.4	1.8	26.8	830
3x70 sm	19x2.22	1.4	1.9	30.2	1050
3x95 sm	19x2.57	1.6	2	33.8	1430
3x120 sm	37x2.08	1.6	2.1	36.4	1710
3x150 sm	37x2.3	1.8	2.2	40.5	2090
3x185 sm	37x2.57	2	2.4	45.2	2520
3x240 sm	37x2.93	2.2	2.6	52	3260
3x300 sm	37x34/3	2.4	2.7	59	4010
3x16+25 rm	7x7 - 2.14x1.7	1 - 1.2	1.8	26.2	904



3x16+35 sm	7x7 - 2.52x1.7	1 - 1.2	1.8	28.5	1080
3x25/50 sm	19x- 1.83 7x2.14	1.2 - 1.4	1.8	27.6	925
3x35/70 sm	19x- 2.22 7x1.52	1.2 - 1.4	1.9	31	1180
3x50/95 sm	19x- 2.58 19x1.83	1.4 - 1.6	2.1	34.7	1630
3x70/120 sm	37x- 2.08 19x2.22	1.4 - 1.6	2.2	38.2	1980
3x70/150 sm	37x- 2.3 19x2.22	1.4 - 1.8	2.3	44	2360
3x95/185 sm	37x- 2.57 19x2.57	1.6- 2.0	2.4	47.4	2890
3x120/240 sm	37x- 2.93 37x2.08	1.6 - 2.2	2.5	53.6	3722
4x50 sm	19x1.83	1.4	1.9	30.6	1090
4x70 sm	19x2.22	1.4	2	34.2	1400
4x95 sm	19x2.57	1.6	2.1	38.4	1880
4x120 sm	37x2.08	1.6	2.2	41.5	2260
4x150 sm	37x2.3	1.8	2.4	45.5	2790
4x185 sm	37x2.57	2	2.6	50.5	3370
4x240 sm	37x2.93	2.2	2.8	59	4350