

کابل‌های قدرت آلومینیومی تک و چند رشته‌ای با عایق XLPE و روکش PVC

NA2XY 0.6 / 1 KV

سایز	قطر * تعداد رشته	ضخامت عایق	ضخامت روکش	قطر کلی تقریبی	وزن تقریبی
mm ²	N x dmm	mm	mm	mm	Kg/km
1x16 rm	7x1.7	0.7	1.4	9.5	116
1x25 rm	7x2.14	0.9	1.4	11.2	166
1x35 rm	7x2.52	0.9	1.4	12.1	204
1x50 rm	19x1.78	1	1.4	13.3	256
1x70 rm	19x2.17	1.1	1.4	15.3	336
1x95 rm	19x2.52	1.1	1.5	17.2	445
1x120 rm	37x2.03	1.2	1.5	18.5	546
1x150 rm	37x2.25	1.4	1.6	20.6	670
1x185 rm	37x2.52	1.6	1.6	22.5	820
1x240 rm	37x2.88	1.7	1.8	26.2	1060
1x300 rm	61x2.50	1.8	1.9	29.2	1290
1x400 rm	61x2.85	2	2	31.4	1600
1x500 rm	61x3.2	2.2	2.1	35.6	2080
3x50 sm	19x1.83	1	1.8	25.1	720
3x70 sm	19x2.22	1.1	1.9	28.4	950
3x95 sm	19x2.57	1.1	2	31.5	1220
3x120 sm	37x2.08	1.2	2.1	35	1510
3x150 sm	37x2.3	1.4	2.2	39	1860
3x185 sm	37x2.57	1.6	2.3	43.2	2320
3x240 sm	37x2.93	1.7	2.6	49	2950
3x300 sm	61x2.65	1.8	2.7	55.2	3660
3x25+16 rm	7x2.14 7x1.7	0.9 - 0.7	1.8	24.2	780



3x35+16 rm	7x2.52 7x1.7	0.9- 0.7	1.8	26.2	940
3x50+25 sm	19x- 1.83 7x2.14	1 - 0.9	1.8	26.2	860
3x70+35 sm	19x- 2.22 7x1.52	1.1 - 0.9	1.9	29.4	1160
3x95+50 sm	19x- 2.58 19x1.83	1.1 - 1	2.1	32.5	1520
3x120+70 sm	37x- 2.08 19x2.22	1.2 - 1.1	2.2	36.2	1910
3x150+70 sm	37x- 2.3 19x2.22	1.4 - 1.1	2.3	41.2	2280
3x185+95 sm	37x- 2.57 19x2.57	1.6 - 1.1	2.5	44.4	2840
3x240+120 sm	37x- 2.93 37x2.08	1.7 - 1.2	2.7	51.2	3520
4x50 sm	19x1.83	1	1.8	28.2	940
4x70 sm	19x2.22	1.1	2	31.5	1250
4x95 sm	19x2.57	1.1	2.1	35	1640
4x120 sm	37x2.08	1.2	2.2	39	2050
4x150 sm	37x2.3	1.4	2.4	43.4	2500
4x185 sm	37x2.57	1.6	2.5	48	3130
4x240 sm	37x2.93	1.7	2.7	55.4	4010