

کابل‌های ابزار دقیق مقاوم در برابر حریق با نوار MICA GLASS با عایق LSF0H تکی و کلی مسلح با زره فولادی با روکش

RE-2X(st)HRH-PIMF 300 / 500 V

سایز	قطر * تعداد رشته	ضخامت عایق	ضخامت بدینگ	قطر مفتول گالوانیزه	ضخامت روکش	قطر کلی تقریبی	وزن تقریبی
mm ²	N x d mm	mm	mm	mm	mm	mm	Kg/km
0.75 mm ² (stranded)							
1x2x0.75	7x0.37	0.6	0.9	0.9	1.4	12.2	208
2x2x0.75	7x0.37	0.6	0.9	0.9	1.4	18.2	464
5x2x0.75	7x0.37	0.6	1.2	1.2	1.5	23	830
10x2x0.75	7x0.37	0.6	1.2	1.2	1.7	29.5	1420
15x2x0.75	7x0.37	0.6	1.3	1.6	1.7	33.8	1850
20x2x0.75	7x0.37	0.6	1.3	1.6	1.8	37.5	2440
30x2x0.75	7x0.37	0.6	1.5	1.6	1.9	46	3180
1mm ² (stranded)							
1x2x1	7x0.43	0.6	1.1	0.9	1.4	13	222
2x2x1	7x0.43	0.6	1.1	0.9	1.5	17.7	484
5x2x1	7x0.43	0.6	1.2	1.2	1.6	22.6	860
10x2x1	7x0.43	0.6	1.3	1.6	1.8	29.1	1460
15x2x1	7x0.43	0.6	1.5	1.6	1.9	33.5	1880
20x2x1	7x0.43	0.6	1.7	2	2	38	2470
30x2x1	7x0.43	0.6	2	2	2.2	45	3250
1.5 mm ² (stranded)							
1x2x1.5	7x0.52	0.6	1.1	0.9	1.4	13.5	330
2x2x1.5	7x0.52	0.6	1.1	0.9	1.5	20.8	710
5x2x1.5	7x0.52	0.6	1.2	1.2	1.6	25.4	1160
10x2x1.5	7x0.52	0.6	1.3	1.6	1.7	33.4	1820



15x2x1.5	7x0.52	0.6	1.5	1.6	1.9	38.2	2500
20x2x1.5	7x0.52	0.6	1.5	1.6	1.9	42.8	2980
30x2x1.5	7x0.52	0.6	2	2	2.2	51.8	4480
2.5 mm ² (stranded)							
1x2x2.5	7x0.67	0.7	1.2	1.2	1.5	14.5	412
2x2x2.5	7x0.67	0.7	1.2	1.2	1.6	20.6	790
5x2x2.5	7x0.67	0.7	1.3	1.6	1.7	26.4	1280
10x2x2.5	7x0.67	0.7	1.5	1.6	1.9	35.4	2140
15x2x2.5	7x0.67	0.7	1.7	2	2	41	3010
20x2x2.5	7x0.67	0.7	1.7	2	2.1	48	3880
30x2x2.5	7x0.67	0.7	2	2.5	2.5	56.6	5580